

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (currently amended): A laser light source comprising:

a semiconductor light-emitting device for emitting light;

an external resonator including a wavelength selector which selects a wavelength of said light;

wherein a stripe is formed in said semiconductor light-emitting device so that it is oblique to one end facet, which does not constitute said external resonator, of the two cleaved end facets of said semiconductor light-emitting device; and

said one end facet of said semiconductor light-emitting device has a coating which becomes an antireflection coating with respect to the selected wavelength;

wherein an optical waveguide device is coupled to said semiconductor light-emitting device or wavelength selector;

said wavelength selector has a function of returning the wavelength-selected light to said semiconductor light-emitting device and is disposed on one side of said semiconductor light-emitting device;

said optical waveguide device is disposed on the other side of said semiconductor light-emitting device; and

said external resonator is constituted by an end facet, on the opposite side from said semiconductor light-emitting device, of said optical waveguide device, and said wavelength selector.

2. (original): The laser light source as set forth in claim 1, wherein  
said wavelength selector comprises two wavelength selectors, disposed on both sides of  
said semiconductor light-emitting device one by one, and having a function of returning the  
wavelength-selected light to said semiconductor light-emitting device; and

said external resonator is constituted by said two wavelength selectors.

3. (original): The laser light source as set forth in claim 1, wherein  
said wavelength selector has a function of returning the wavelength-selected light to said  
semiconductor light-emitting device; and

*B1 cat-*  
said external resonator is constituted by said wavelength selector and an end facet, on the  
opposite side from said wavelength selector, of said semiconductor light-emitting device.

4. (original): The laser light source as set forth in claim 3, wherein said stripe has a bent  
portion and is formed perpendicular to said end facet, on the opposite side from said wavelength  
selector, of said semiconductor light-emitting device.

~~5. (canceled).~~

6. (original): The laser light source as set forth in claim 2, wherein an optical waveguide  
device is coupled to said semiconductor light-emitting device or wavelength selector.

7. (original): The laser light source as set forth in claim 3, wherein an optical waveguide  
device is coupled to said semiconductor light-emitting device or wavelength selector.

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No. 10/000,123

8. (original): The laser light source as set forth in claim 4, wherein an optical waveguide device is coupled to said semiconductor light-emitting device or wavelength selector.

~~9.~~ (canceled).

10. (currently amended): The laser light source as set forth in claim ~~[[5]]~~1, wherein said optical waveguide device has a wavelength converting function.

11. (currently amended): The laser light source as set forth in claim ~~[[9]]~~1, wherein said optical waveguide device has a wavelength converting function.

12. (currently amended): The laser light source as set forth in claim ~~[[5]]~~1, wherein the width of the wavelength selected by said wavelength selector is nearly the same as an allowable phase-matching wavelength width for wavelength conversion which is performed by said optical waveguide device having a wavelength converting function.

*B1 cut.*  
13. (currently amended): The laser light source as set forth in claim ~~[[9]]~~1, wherein the width of the wavelength selected by said wavelength selector is nearly the same as an allowable phase-matching wavelength width for wavelength conversion which is performed by said optical waveguide device having a wavelength converting function.

14. (original): The laser light source as set forth in claim 11, wherein the width of the wavelength selected by said wavelength selector is nearly the same as an allowable phase-matching wavelength width for wavelength conversion which is performed by said optical waveguide device having a wavelength converting function.

15. (currently amended): The laser light source as set forth in claim ~~[[5]]~~1, wherein said optical waveguide device is disposed in said external resonator.

~~16.~~ (canceled).

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No. 10/000,123

17. (original): The laser light source as set forth in claim 11, wherein said optical waveguide device is disposed in said external resonator.

18. (original): The laser light source as set forth in claim 12, wherein said optical waveguide device is disposed in said external resonator.

19. (original): The laser light source as set forth in claim 15, wherein an end facet of said optical waveguide device that constitutes said external resonator is cut perpendicular to a direction where an optical waveguide of said optical waveguide device extends.

20. (original): The laser light source as set forth in claim 15, wherein an end facet of said optical waveguide device that does not constitute said external resonator is cut oblique to a direction where an optical waveguide of said optical waveguide device extends.

*B,*  
*cat.* 21. (currently amended): The laser light source as set forth in claim ~~[[5]]~~1, wherein said optical waveguide is coupled directly to said semiconductor light-emitting device or wavelength selector.

22. (canceled).

23. (original): The laser light source as set forth in claim 11, wherein said optical waveguide is coupled directly to said semiconductor light-emitting device or wavelength selector.

24. (original): The laser light source as set forth in claim 12, wherein said optical waveguide is coupled directly to said semiconductor light-emitting device or wavelength selector.

AMENDMENT UNDER 37 C.F.R. § 1.111  
U.S. Application No. 10/000,123

25. (original): The laser light source as set forth in claim 15, wherein said optical waveguide is coupled directly to said semiconductor light-emitting device or wavelength selector.

26. (original): The laser light source as set forth in claim 19, wherein said optical waveguide is coupled directly to said semiconductor light-emitting device or wavelength selector.

27. (original): The laser light source as set forth in claim 20, wherein said optical waveguide is coupled directly to said semiconductor light-emitting device or wavelength selector.

28. (original): The laser light source as set forth in claim 1, wherein said wavelength selector is a waveguide type wavelength selector having a reflection Bragg grating in an optical waveguide portion.

29. (original): The laser light source as set forth in claim 28, wherein said wavelength selector and said semiconductor light-emitting device are coupled directly with each other.

30. (currently amended): The A laser light source as set forth in claim 1, comprising:  
a semiconductor light-emitting device for emitting light;  
an external resonator including a wavelength selector which selects a wavelength of said  
light;

wherein a stripe is formed in said semiconductor light-emitting device so that it is oblique  
to one end facet, which does not constitute said external resonator, of the two cleaved end facets  
of said semiconductor light-emitting device; and

said one end facet of said semiconductor light-emitting device has a coating which becomes an antireflection coating with respect to the selected wavelength;

wherein

said external resonator is constituted by a mirror, disposed to face one end facet of said semiconductor light-emitting device, and the other end facet of said semiconductor light-emitting device; and

said wavelength selector comprises a narrow-band pass filter disposed between said mirror and said semiconductor light-emitting device.

31. (currently amended): ~~The A~~ laser light source ~~as set forth in claim 1~~, further comprising:

a semiconductor light-emitting device for emitting light;

an external resonator including a wavelength selector which selects a wavelength of said light;

wherein a stripe is formed in said semiconductor light-emitting device so that it is oblique to one end facet, which does not constitute said external resonator, of the two cleaved end facets of said semiconductor light-emitting device;

said one end facet of said semiconductor light-emitting device has a coating which becomes an antireflection coating with respect to the selected wavelength; and

a drive circuit that drives said semiconductor light-emitting device with high-frequency superposition.

32. (original): The laser light source as set forth in claim 30, further comprising a drive circuit that drives said semiconductor light-emitting device with high-frequency superposition.

33. (previously presented): The laser light source as set forth in claim 1, wherein  
a longitudinal mode width of said external resonator is less than the width of the  
wavelength selected by said wavelength selector; and  
said laser light source is operated in a multi-longitudinal mode which is within the width  
of said selected wavelength by high-frequency superposition.

34. (previously presented): The laser light source as set forth in claim 30, wherein  
a longitudinal mode width of said external resonator is less than the width of the  
wavelength selected by said wavelength selector; and  
said laser light source is operated in a multi-longitudinal mode which is within the width  
of said selected wavelength by high-frequency superposition.

131  
cont.  
35. (original): The laser light source as set forth in claim 31, wherein  
a longitudinal mode width of said external resonator is less than the width of the  
wavelength selected by said wavelength selector; and  
said laser light source is operated in a multi-longitudinal mode which is within the width  
of said selected wavelength by said high-frequency superposition.

36. (previously presented): The laser light source as set forth in any one of the preceding  
claims, further comprising temperature control means for maintaining the devices, which  
constitute said external resonator, at a predetermined temperature.

---